

What is claimed is:

- 1 1. An electrostatic comb drive comprising
2 a base;
3 a movable element movably connected to the base and configured to move
4 from a first position to a second position relative to the base;
5 a spring disposed between the base and the movable element and
6 configured to provide a potential energy maximum between the first position and the
7 second position;
8 a fixed finger attached to the base, the fixed finger having a first portion
9 proximate to the base and disposed between the base and a second portion of the fixed
10 finger; and
11 a movable finger attached to the movable element, the movable finger
12 having a third portion proximate to the movable element and disposed between the
13 movable element and a fourth portion of the movable finger, a first capacitance arising
14 between the fixed finger and the movable finger when the second portion is adjacent to the
15 fourth portion and a second capacitance arising between the fixed finger and the movable
16 finger when the second portion is adjacent to the third portion, the first capacitance being
17 greater than the second capacitance.
- 1 2. The electrostatic comb drive of claim 1 wherein the second portion
2 is wider than the first portion and the fourth portion is wider than the third portion.
- 1 3. The electrostatic comb drive of claim 1 wherein the second portion
2 is at least three times as wide as the first portion.
- 1 4. The electrostatic comb drive of claim 1 wherein the first portion is
2 less than four microns wide and the second portion is greater than six microns wide.
- 1 5. The electrostatic comb drive of claim 1 wherein the second portion
2 is taller than the first portion and the fourth portion is taller than the third portion.
- 1 6. The electrostatic comb drive of claim 1 wherein the second portion
2 is at least three times as tall as the first portion.

1 7. The electrostatic comb drive of claim 1 further comprising a
2 mechanical latch to latch the movable element in one of the first position and the second
3 position.

1 8. The electrostatic comb drive of claim 1 wherein the mechanical
2 latch is combined with the spring to form a latching spring arm.

1 9. The electrostatic comb drive of claim 1 further comprising:
2 a second movable finger attached to the movable element and extending
3 away from the movable element in a direction opposite to the movable finger; and
4 a second fixed finger proximate to the second movable finger and
5 extending from the base toward the movable element, wherein the second movable finger
6 is electrically coupled to the movable finger and the second fixed finger is electrically
7 coupled to the fixed finger.

1 10. The electrostatic comb drive of claim 1 further comprising a voltage
2 supply electrically coupled to the fixed finger with a first electrical connection and
3 electrically coupled to the movable finger with a second electrical connection, the voltage
4 supply configured to provide a first voltage pulse to toggle the movable element from the
5 first position to the second position and to provide a second voltage pulse to toggle the
6 movable element from the second position to the first position wherein the first voltage
7 pulse and the second voltage pulse are essentially the same.

1 11. An electrostatic comb drive comprising:
2 a base;
3 a movable element movably connected to the base and configured to move
4 from a first position to a second position relative to the base;
5 a fixed finger attached to the base, the fixed finger having a first narrow
6 portion proximate to the base and a first wide portion distal from the base; and
7 a movable finger attached to the movable element, the movable finger
8 having a second narrow portion proximate to the movable portion and a second wide
9 portion distal from the movable element.

1 12. The electrostatic comb drive of claim 11 further comprising a
2 latching spring arm.

1 13. The electrostatic comb drive of claim 11 further comprising an
2 overlap portion extending away from the first wide portion toward the movable element,
3 the overlap portion being at least partially adjacent to the second wide portion in one of
4 the first position and the second position.

1 14. The electrostatic comb drive of claim 11 further comprising an
2 overlap portion extending away from the second wide portion toward the base, the overlap
3 portion being at least partially adjacent to the first wide portion in one of the first position
4 and the second position.

1 15. The electrostatic comb drive of claim 11 wherein a center portion of
2 the second wide portion has been removed.

1 16. An electrostatic comb drive comprising:
2 a base;
3 a movable element;
4 a first latching spring arm movably connecting the movable element to the
5 base;
6 a second latching spring arm movably connecting the movable element to
7 the base, the first latching spring arm and the second latching spring providing a first
8 potential energy minimum at a first stable position of the movable element relative to the
9 base and providing a second potential energy minimum at a second stable position of the
10 movable element relative to the base, and providing a potential energy maximum between
11 the first stable position and the second stable position;
12 a fixed finger attached to the base, the fixed finger having a first narrow
13 portion proximate to the base and a first wide portion distal from the base, the first wide
14 portion being at least twice as wide as the first narrow portion; and
15 a movable finger attached to the movable element, the movable finger
16 having a second narrow portion proximate to the movable portion and a second wide
17 portion distal from the movable element, the second wide portion being at least twice as
18 wide as the first narrow portion.

1 17. A method of fabricating an electrostatic comb drive, the method
2 comprising:
3 providing a wafer having

4 a superstrate,
5 a substrate, and
6 a bonding layer bonding the superstrate to the substrate,
7 masking a set of fixed fingers in the superstrate, a fixed finger having a first
8 narrow portion proximate to a base of the electrostatic comb drive and a first wide portion
9 extending from the first narrow portion away from the base;
10 masking a set of movable fingers in the superstrate, a movable finger
11 having a second narrow portion proximate to a movable element of the electrostatic comb
12 drive and a second wide portion extending from the second narrow portion away from the
13 movable element toward the base; and
14 removing the bonding layer from beneath at least the movable element and
15 the set of movable fingers.

1 18. A device made according to the method of claim 17.

1 19. An electrostatic comb drive comprising:
2 a base;
3 a movable element;
4 a fixed finger attached to the base, the fixed finger having a first short
5 portion proximate to the base and a first tall portion distal from the base; and
6 a movable finger attached to the movable element, the movable finger
7 having a second short portion proximate to the movable element and a second tall portion
8 distal from the movable element.

1 20. The electrostatic comb drive of claim 19 wherein a portion of the
2 first tall portion is adjacent to the second tall portion when the movable element is in a
3 first stable position.

1 21. The electrostatic comb drive of claim 19 wherein the first tall
2 portion is at least three times as high as the first short portion and the second tall portion is
3 at least twice as high as the second short portion.

1 22. A method of fabricating an electrostatic comb drive, the method
2 comprising:
3 providing a wafer having
4 a superstrate,

5 a substrate, and
6 a bonding layer bonding the superstrate to the substrate,
7 exposing a first etch region of the wafer;
8 etching the superstrate to a selected thickness in the first etch region;
9 masking a comb finger area of the wafer, the comb finger area including at
10 least a portion of the first etch region;
11 etching through the superstrate to define a comb finger having a first
12 thickness in the first etch region and a second thickness in a thick region, the first
13 thickness being less than the second thickness.

1 23. The method of claim 22 further comprising a step, after etching
2 through the superstrate, of
3 removing the bonding layer from beneath at least the comb finger area.

1 24. The method of claim 22 wherein the exposing step occurs
2 subsequent to the masking step.

1 25. A method of operating an electrostatic comb drive having a first
2 stable position and a second stable position, the method comprising:
3 from the first stable position, applying an actuating pulse to accelerate a
4 movable element of the electrostatic comb drive toward the second stable position;
5 displacing the movable element beyond a potential energy maximum
6 between the first stable position and the second stable position while
7 maintaining the actuating pulse to decelerate the movable element;
8 removing the actuating pulse; and
9 latching the movable element in the second stable position.

1 26. The method of claim 25 wherein the actuating pulse does not
2 exceed 40 volts.

1 27. The method of claim 25 wherein the actuating pulse is a square
2 voltage pulse.

1 28. The method of claim 25 further comprising steps, after the latching
2 step, of:

3 applying a second actuating pulse to accelerate the movable element toward
4 the first stable position;
5 displacing the movable element beyond the potential energy maximum;
6 maintaining the actuating pulse to decelerate the movable element, wherein
7 the second actuating pulse is substantially identical to the actuating pulse;
8 removing the second actuating pulse; and
9 latching the movable element in the first stable position.

1 29. The method of claim 28 wherein the first actuating pulse is a square
2 wave pulse.

1 30. A method of initializing an electrostatic comb drive having a first
2 stable position and a second stable position, the method comprising:
3 applying a voltage between a set of movable fingers and a set of fixed
4 fingers;
5 maintaining the voltage to draw a movable element of the electrostatic
6 comb drive from one of the first stable position and the second stable position to a position
7 between a potential energy maximum and the first stable position;
8 releasing the voltage so that the movable element moves to the first stable
9 position.

1 31. A method of designing an actuation pulse for a micro-electro-
2 mechanical system ("MEMS") device, the method comprising:
3 determining a first actuation window in a time-voltage plane, the first
4 actuation window corresponding to first limits in pulse duration and applied voltage for
5 switching a movable element of the MEMS device from a first position to a second
6 position for the movable element fabricated with a first critical dimension limit from a
7 base of the MEMS device;
8 determining a second actuation window in the time-voltage plane, the
9 second actuation window corresponding to second limits in pulse duration and applied
10 voltage for switching the movable element of the MEMS device from the first position to
11 the second position for the movable element fabricated with a second critical dimension
12 limit from the base of the MEMS device;
13 overlying the first actuation window and the second actuation window to
14 result in a common actuation window; and

1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	2101	2102	2103	2104	2105	2106	2107	2108	2109	2110	2111	2112	2113	2114	2115	2116	2117	2118	2119	2120	2121	2122	2123	2124	2125	2126	2127	2128	2129	2130	2131	2132	2133	2134	2135	2136	2137	2138	2139	2140	2141	2142	2143	2144	2145	2146	2147	2148	2149	2150	2151	2152	2153	2154	2155	2156	2157	2158	2159	2160	2161	2162	2163	2164	2165	2166	2167	2168	2169	2170	2171	2172	2173	2174	2175	2176	2177	2178	2179	2180	2181	2182	2183	2184	2185	2186	2187	2188	2189	2190	2191	2192	2193	2194	2195	2196	2197	2198	2199	2200	2201	2202	2203	2204	2205	2206	2207	2208	2209	2210	2211	2212	2213	2214	2215	2216	2217	2218	2219	2220	2221	2222	2223	2224	2225	2226	2227	2228	2229	2230	2231	2232	2233	2234	2235	2236	2237	2238	2239	2240	2241	2242	2243	2244	2245	2246	2247	2248	2249	2250	2251	2252	2253	2254	2255	2256	2257	2258	2259	2260	2261	2262	2263	2264	2265	2266	2267	2268	2269	2270	2271	2272	2273	2274	2275	2276	2277	2278	2279	2280	2281	2282	2283	2284	2285	2286	2287	2288	2289	2290	2291	2292	2293	2294	2295	2296	2297	2298	2299	2300	2301	2302	2303	2304	2305	2306	2307	2308	2309	2310	2311	2312	2313	2314	2315	2316	2317	2318	2319	2320	2321	2322	2323	2324	2325	2326	2327	2328	2329	2330	2331	2332	2333	2334	2335	2336	2337	2338	2339	2340	2341	2342	2343	2344	2345	2346	2347	2348	2349	2350	2351	2352	2353	2354	2355	2356	2357	2358	2359	2360	2361	2362	2363	2364	2365	2366	2367	2368	2369	2370	2371	2372	2373	2374	2375	2376	2377	2378	2379	2380	2381	2382	2383	2384	2385	2386	2387	2388	2389	2390	2391	2392	2393	2394	2395	2396	2397	2398</
------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	--------